



ICC-ES PMG Product Certificate



PMG-1238

Effective Date: March 2023

This listing is subject to re-examination in one year.



www.icc-es-pmg.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00 – PLUMBING
Section: 22 13 16 – Sanitary Waste and Vent Piping

Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: EZ-Flex Couplings

Listee: ProVent Systems, Inc.
1355 Capital Circle
Lawrenceville, Georgia 30043
www.proventsystems.com

Compliance with the following codes:

2021, 2018, 2015, 2012 and 2009 *International Plumbing Code® (IPC)*
2021, 2018, 2015, 2012 and 2009 *International Residential Code (IRC)*
2021, 2018, 2015, 2012 and 2009 *Uniform Plumbing Code® (UPC)**

**Copyrighted publication of the International Association of Plumbing and Mechanical Officials*

Compliance with the following standards:

ASTM C1173-2022, Flexible Transition Couplings for Underground Piping Systems
CSA B602-20, Mechanical Couplings for Drain, Waste, and Vent Pipe and Sewer Pipe

Identification:

Couplings shall be permanently marked with the manufacturer's name or the manufacturer's registered trademark, model number, nominal pipe size (NPS), pipe material(s) for which the coupling is designed, standard designation, and ICC-ES PMG listing mark.

Models:

EZ-Flex Coupling

EZ Flex Couplings are designed for the connection of PVC to PVC and PVC to Cast Iron DWV and sewer pipe.

Listings are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the listing or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this listing, or as to any product covered by the listing.

EZ-Flex coupling consists of a one-piece elastomeric polyvinyl chloride (PVC) gasket with a 300 series stainless steel clamp. The male end is solvent cemented to the rigid coupling; the female end is connected with either PVC or cast iron pipe with sealing by mechanical clamp.

Table 1 – EZ FLEX COUPLINGS

Part Number	Description
P1514	1-1/2" PVC to 1-1/4" TUBULAR
P15470	1-1/2" PVC to 1-1/2" TUBULAR
P25470	2" E-Z FLEX COUPLING
P35470	3" E-Z FLEX COUPLING
P35470-D	3" E-Z FLEX DOUBLE COUPLING
P45470	4" E-Z FLEX COUPLING
P45470-D	4" E-Z FLEX DOUBLE COUPLING
P65470	6" E-Z FLEX COUPLING

1 inch = 25.4 mm

Conditions of Listing:

1. The EZ Flex Couplings must be installed in accordance with this listing, the applicable code and the manufacturer's published installation instructions. The instructions within this listing must govern if there are any conflicts between the manufacturer's published instructions and this listing.
2. Use of EZ Flex couplings above ground is subject to the approval of the code official.
3. Couplings are under a quality control program with annual inspections by ICC-ES.